

Continuing Project

# Quantifying Silvicultural Treatment Effect on Lumber Quantity and Quality in Loblolly Pine

CAFS 21.88

Anjila Lamichhane (UGA), Joe Dahlen (UGA), Corey Green (VT),  
Cristian

Montes (Rayonier), Bronson Bullock (UGA), Tom Eberhardt (USFS)

Presenter: Joseph Dahlen - UGA



# FMRC Intensively Managed Plantation (IMP) Trial



3 Treatments

A. Control

B. Light thinning


C. Heavy thinning with  
pruning in butt log

Treatments applied when  
trees reached 40-46 ft

105 Total Trees

5 Stands

7 Trees/Plot





Logs &  
resulting lumber  
tracked thru sawmill

- Treatment
- Stand
- Tree #
- Log #
- Position within log



# Lumber



- Partnering mill only cuts 2×4 & 2×6 lumber
- 1099 total pieces cut
- Lumber left in 16.6' lengths for tracking

- Lumber not graded or trimmed by mill





# Lumber visually graded by certified SPIB graders in Athens


Ashley West, Daniel Carroll



# Lumber Test Span

- ASTM testing standards
- Span to depth ratio of 17:1
- 2×4 span to depth = 59.5"
- 2×6 span = 93.5"
- 16' lumber (192")

Worst defect predicted and included randomly within the test span



# Non-destructive Testing

## Acoustic Velocity

Sound velocity via  
impact and microphone  
Wood Density

$MOE_{dyn} = \text{density} * \text{velocity}^2$



# Lumber Imaging for Knots




**Industry grading systems operate up to 4500 feet/second**

**UGA's setup is a little slower...**



# Lumber Imaging for Knots



**>88,000 images  
with 4 sides of  
each piece  
images**



# Lumber Imaging for Knots – S.S. Grade



# Lumber Imaging for Knots – No. 1 Grade





# Lumber Imaging for Knots – No. 2 Grade





# Lumber Imaging for Knots – No. 3 Grade



# Lumber Imaging for Knots – No. 4 Grade





# Destructive Testing






# Destructive Testing






# Destructive Testing

371



# Strong relationship between static and dynamic MOE



The worst outlier for static vs dynamic MOE had few knots, high velocity, high SG, but a lot of wane



# Lumber Grade by Treatment and Log Position

SS = 0, 1 = 1...

<b>Treatment</b>	<b>Log 1</b>	<b>Log 2</b>	<b>Log 3</b>
Control	1.50	1.93	2.25
Light Thinning	1.19	1.82	2.39
Heavy Thinning + Pruning	1.08	1.83	2.69





# Static MOE<sub>15</sub> (GPa) by Treatment and Log Position

Treatment	Log 1	Log 2	Log 3
Control	8.76	8.28	7.45
Light Thinning	9.33	8.31	7.40
Heavy Thinning + Pruning	8.89	7.85	6.80



# Static MOE<sub>15</sub> (GPa) by Treatment and Grade

## Light and Heavy Thinning significantly different

Treatment	Grade				No. 4
	SS	No. 1	No. 2	No. 3	
Control	9.97	8.64	8.35	7.21	7.32
Light Thinning	10.68	8.73	8.21	7.60	6.52
Heavy Thinning + Pruning	9.82	8.11	7.95	6.93	6.80



# Treatments are different but we are bumping up to sample size limitation

3 Treatments

A. Control

B. Light thinning


C. Heavy thinning with pruning in butt log

Treatments applied when trees reached 40-46 ft

105 Total Trees -  
**35/treatment**

5 Stands

7 Trees/Plot





# How to get more trees/treatment

## How: hire stronger people!





# How to get more trees/treatment

## How: process the logs into lumber ourselves with new technology!






# Deliverables and Company Benefits



Lumber quality and quantity information as a result of silviculture from a designed experiment

Evaluation on the impacts of 2 thinning regimes relative to no thinning

# Thank You and Questions?



- NSF CAFS
- Wood Quality Consortium
- Forest Modeling Research Cooperative
- Plantation Management Research Cooperative
- Daniel Carroll and Ashlyn West from Southern Pine Inspection Bureau
- AI images via Adobe





# Control Treatment Unthinned





# Light Thinning Treatment ~1/2 trees removed





# Heavy Thinning Treatment + Butt Log Pruning

$\sim 3/4$  trees removed





# Trees cut into 5 m logs






# Disks collected for whole-disk and ring-by-ring properties at 0,5,10,15 m height levels



# Log Acoustic Velocity by Treatment and Log Position



# Log Acoustic Velocity by Treatment and Log Position

Treatment	# of Logs	Log 1 AV	Log 3 AV	
		(m/s)	Log 2 AV (m/s)	(m/s)
Control	82	3101	3171	2985
Light Thinning	91	3092	3132	2984
Heavy Thinning + Pruning	93	2971	2960	2738
Overall	266	3055	3086	2885





# Lumber Yield by Treatment (Preliminary)

## FMRC scaling data to per acre basis

Treatment	2x4		2x6	
	MBF	Mean Grade <sup>1</sup>	MBF	Mean Grade <sup>1</sup>
Control	1.36	1.88	1.82	1.66
Light Thinning	1.37	1.93	3.38	1.44
Heavy Thinning + Pruning	1.14	2.23	5.40	1.41

<sup>1</sup>Mean grade is the average grade calculated  
Select Structural = 0, No. 1 = 1, No. 2 = 2, No. 3 = 3,  
No. 4 = 4



# Lumber Dynamic MOE (GPa) (Acoustic Velocity method) by Treatment and Grade

Treatment	Grade				No. 4
	SS	No. 1	No. 2	No. 3	
Control	11.20	10.02	10.03	8.61	8.40
Light Thinning	12.39	10.36	9.89	9.16	8.33
Heavy Thinning + Pruning	11.69	9.58	9.57	8.58	8.30



# Lumber Dynamic MOE (GPa) (Acoustic Velocity method) by Treatment and Log Position

Treatment	Log 1	Log 2	Log 3
Control	10.04	9.99	9.91
Light Thinning	10.78	10.27	9.12
Heavy Thinning + Pruning	10.35	9.73	8.53

